

Maven digital repeater PS EMEA-APAC Exo repeater for Critical Comms

Datasheet version 2.9

**Outstanding
Performance**

**End to end
Digital platform**

**Always
Future-proof**

**Overall
Cost efficiency**

**More
Sustainable**

Maven Wireless offers new solutions for wireless coverage in all parts of the world. Our products are end to end digital and future-proof, comes with the best performance and cost efficiency you can find. We also have high marks on sustainability and a burning passion for making our customers and end-users life safer, better and easier by securing 100% wireless coverage.

**Exo high power digital repeater for
critical communications and public
safety**



Exo off air repeater specification

General

Mains power	85 – 264 VAC, -72 – -36 VDC optional
Power consumption	200 W max fully loaded
Management	Ethernet 10/100/1000, micro USB, USB accessory connector
Remote Access	Optional 4G modem
Operating temperature	-25 to +55 °C
Ingress protection	IP66
RF interface	Up to 2 bands in one enclosure
Antenna port	4.3-10 or 7/16 optional
System Gain	60 to 90 dB in 0.1 dB steps †
Gain flatness	1 dB pp
Noise figure	< 3 dB at max gain

RF Parameters

RF input range	+17 dBm, non-destructive
----------------	--------------------------

Frequencies*

Band	Uplink (MHz)	Downlink (MHz)	Operation bandwidth	Composite output power DL/UL	Technologies
400	380-470	380-470	5 MHz	40 dBm / 40 dBm	TETRA TMO
400	Other frequencies available on request		5 MHz **	40 dBm / 40 dBm	TETRA TMO
900-R	873-880	918-925	7 MHz	43 dBm / 30 dBm	GSM-R

** DQPSK Typically 5 MHz BW with 10 MHz duplex spacing, normally DL 10 MHz above UL. For D-BOS 6.5 MHz passband available.

Available Filters / Channels

Channel selective	Max 64 various bandwidths
Sub-band selective	Max 32 various bandwidths 0-5 MHz / 6.5 for D-BOS
Band Selective	5.5 MHz or 6.5 MHz for D-BOS

Mechanical

Dimensions (height, width, depth)	670 x 383 x 270 mm
-----------------------------------	--------------------

Weight	max 23 kg
--------	-----------

Standard & Approvals

EMC & safety	Low voltage directive 73/23/EEC
--------------	---------------------------------

EMC directive 2004/108/EC	R&TTE directive 1999/5/EC
---------------------------	---------------------------

†) Note for TETRA technology, maximum gain is 80 dB,

*) Various frequency combinations in the same enclosure are available. Contact Maven Wireless for more information.
Note: All parameters are subject to change.

**) DQPSK Typically 5 MHz BW with 10 MHz duplex spacing, normally DL 10 MHz above UL. For D-BOS 6.5 MHz passband available.